



Slide Speed Gate



Description

The EA Slide speed gate has been designed with a similar operating principle as the Speed Lane solution. The significant difference of the EA Slide is its glass height being higher at 1400mm as standard, but can be customised to be taller. This design offers a more effective protection of your site by preventing persons 'hurdling' the barrier panels, similar to full-height turnstiles. But it serves to be a aesthetic solution for lobbies of office centers, banks, and other public facilities etc. The high panels prevent item to be carried over the speed gate and offers the opportunity of brand logos to be added on the sliding glass panels. Anti-tailgating is standard and an optional back-up battery is available.

Features

-  30 users p/min
-  0.8s Opening time
-  600mm passage width
-  Two way operation
-  Anti - tailgating

Controlled by

-  Access control system by others
-  Remote or desk operation override is an option

Technical specs

Width, mm	300
Length, mm	980
Height, mm	1400
Weight, kg	Single pass – 288 Two – pass – 469
Mechanism	Motorized
Standard housing	Brushed AISI 304
Available housing	Brushed SS AISI 316 Polished SS AISI 304 Polished SS AISI 316 Powder coated RAL

Electrical specs

Voltage	- from the AC (100-240)V, 50/60Hz; - from a DC source 12 V
Maximum power consumption	155 W per pass